



US009376088B2

(12) **United States Patent**
Sumroy

(10) **Patent No.:** **US 9,376,088 B2**
(45) **Date of Patent:** **Jun. 28, 2016**

(54) **APPARATUS FOR ADAPTING A SEATBELT FOR A CHILD**

USPC 297/482, 481
See application file for complete search history.

(71) Applicant: **Jon Sumroy**, Raanana (IL)

(56) **References Cited**

(72) Inventor: **Jon Sumroy**, Raanana (IL)

U.S. PATENT DOCUMENTS

(73) Assignee: **CARFOLDIO LTD.**, Youngstown, OH (US)

3,136,579 A 6/1964 Hunter
3,258,293 A * 6/1966 Sharp 297/483

(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 29 days.

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **14/131,611**

CZ 2007466 7/2007
DE 20-2004-010-469 9/2004

(Continued)

(22) PCT Filed: **May 28, 2013**

OTHER PUBLICATIONS

(86) PCT No.: **PCT/IL2013/050454**

Vakhnina & Partners, Russian Search Report regarding PCT/IL2013/050454 (2014/150424), Jan. 1, 2016.

§ 371 (c)(1),

(2) Date: **Jan. 8, 2014**

(Continued)

(87) PCT Pub. No.: **WO2013/179283**

PCT Pub. Date: **Dec. 5, 2013**

Primary Examiner — David E Allred

Assistant Examiner — Alexander Harrison

(74) *Attorney, Agent, or Firm* — Robert G. Lev

(65) **Prior Publication Data**

US 2014/0152072 A1 Jun. 5, 2014

Related U.S. Application Data

(60) Provisional application No. 61/652,338, filed on May 29, 2012.

(51) **Int. Cl.**

A47D 15/00 (2006.01)

B60R 22/10 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **B60R 22/105** (2013.01); **B60N 2/2866** (2013.01); **B60R 22/024** (2013.01); **B60R 22/18** (2013.01); **B60R 2022/1818** (2013.01)

(58) **Field of Classification Search**

CPC B60R 22/02; B60R 22/00

(57) **ABSTRACT**

Apparatus for adapting an adult three-point seatbelt for securing a child, the seatbelt comprising a belt extending from above the shoulder to an anchor point connected to chassis of vehicle, and a clasp attached to the chassis on opposite side of an occupant of the seat, such that the belt may be drawn downwards and across the occupant to engage the clasp, thereby restraining the occupant with both sash and lap sections of the seatbelt, the apparatus comprising: a mat with side catches for engaging the lap section of the seatbelt and holding it down over the legs of the child, and a strap fixed to the mat and having a clip at a distal end thereof, for extending behind the child, and the clip for clippably engaging the belt extending from the drum, to bring the sash section of the belt down, over the shoulder of the child.

11 Claims, 6 Drawing Sheets

